

Application No.: 10/767,745**Docket No.: 713-1003****AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1. (Previously presented) A retaining member for holding and supporting an elongated element from a support, said retaining member comprising:
a base portion attachable to the support; and
a holding portion connected to said base portion and comprising a recess for holding the elongated element therein, said recess comprising:
a tubular portion; and
a plurality of spaced ribs extending radially inwardly from said tubular portion to have different radial heights.

2-11. (canceled)

12. (Previously presented) The retaining member as claimed in claim 1, wherein said ribs are elongated in a circumferential direction of said tubular portion.

13. (Previously presented) The retaining member as claimed in claim 12, wherein said base portion is made of a harder plastic material and said ribs and said tubular portion are made of a softer plastic material.

14. (Previously presented) The retaining member as claimed in claim 12, wherein said elongated ribs describe circular or helical curves.

15. (Previously presented) The retaining member as claimed in claim 12, wherein said

Application No.: 10/767,745Docket No.: 713-1003

ribs are disposed at a uniform spacing in an axial direction of said tubular portion.

16. (Previously presented) The retaining member as claimed in claim 12, wherein said ribs include first ribs having a greater radial height and second ribs having a smaller radial height, and wherein said first and second ribs are alternately arranged in an axial direction of said tubular portion.

17. (Previously presented) The retaining member as claimed in claim 12, wherein said ribs include first ribs having a first radial height and second ribs having a second radial height smaller than the first radial height, and wherein a first width of said first ribs at tops thereof is smaller than a second width of said second ribs at tops thereof.

18. (Previously presented) The retaining member as claim in claim 17, wherein the first radial height of said first ribs is greater than the first width at the tops of said first ribs.

19. (Previously presented) The retaining member as claimed in claim 17, wherein the second radial height of said second ribs is smaller than the second width at the tops of said second ribs.

20. (Previously presented) The retaining member as claimed in claim 1, wherein said ribs comprise at least one first rib having a first radial height and a plurality of second ribs having a second radial height smaller than the first radial height;

said holding portion further comprises an elongated slot for allowing insertion of the elongated element into said recess via said elongated slot; and

said elongated slot has opposite elongated edges extending in an axial direction of said tubular portion and said first rib is spaced, in a circumferential direction of said tubular portion, from each of the edges of said elongated slot by at least one of said second ribs.

Application No.: 10/767,745**Docket No.: 713-1003**

21. (Previously presented) The retaining member as claimed in claim 20, wherein said base portion is made of a harder plastic material and said first and second ribs are made of a softer plastic material.

22. (Previously presented) The retaining member as claimed in claim 20, wherein said first and second ribs are elongated in the axial direction of said tubular portion, and alternately arranged in the circumferential direction of said tubular portion with a uniform spacing.

23. (Previously presented) The retaining member as claimed in claim 20, wherein said first and second ribs are elongated in the axial direction of said tubular portion and alternately arranged in the circumferential direction of said tubular portion, and wherein said alternately arranged ribs include at least three said first ribs and at least three said second ribs.

24. (Currently amended) The retaining member as claimed in claim 20, wherein said holding portion includes at least three said first ribs two of which are arranged along the edges of said slot.

25. (Previously presented) The retaining member as claimed in claim 20, wherein a first width of said first rib at a top thereof is smaller than a second width of said second ribs at tops thereof.

26. (Previously presented) The retaining member as claim in claim 25, wherein the first radial height of said first rib is greater than the first width at the top of said first rib.

27. (Previously presented) The retaining member as claimed in claim 25, wherein the second radial height of said second ribs is smaller than the second width at the tops of said second ribs.

Application No.: 10/767,745Docket No.: 713-1003

28. (Previously presented) The retaining member as claimed in claim 20, wherein a top of said first rib describes a convex curve and tops of said second ribs describe concave curves.

29. (Previously presented) The retaining member as claimed in claim 20, further comprising a further holding portion connected to said base portion and comprising a further recess for holding another elongated element therein, said further recess having a smooth inner surface free of ribs or teeth;

wherein said holding portions are positioned on opposite sides of said base portion.

30. (Previously presented) The retaining member as claimed in claim 21, further comprising a resilient contact element adapted to bear against a surface of the support when said base position is attached to the support, said resilient contact element being made from the same plastic material as said first and second ribs.

31. (Previously presented) In combination,
an elongated element; and
a retaining member for holding and supporting said elongated element from a support, said retaining member comprising:

a base portion attachable to the support; and

a holding portion connected to said base portion and comprising a recess holding the elongated element therein, said recess comprising:

a tubular portion; and

a plurality of spaced ribs extending radially inwardly from said tubular portion, said ribs including at least a first rib having a first radial height and at least a second rib having a second radial height smaller than the first radial height;

wherein said elongated element is resiliently supported in said recess by said first rib to be

Application No.: 10/767,745Docket No.: 713-1003

radially spaced from said second rib and said tubular portion, said first rib being elastically deformable to allow said elongated element to come to rest on said second rib without allowing said elongated element to contact said tubular portion and said base portion.

32. (Currently amended) The combination of claim 31, further comprising
[[said]] a support to which said base portion is attached; and
a resilient contact element that bears against the support and spaces said base portion from
said support;

wherein said base portion is made of a harder plastic material whereas said first and second
ribs, said tubular portion and said resilient contact element are made of a softer plastic material.